

SIRIUS



Automatic parts washer.

Washing is carried out automatically by means of upper, lower and side jets through 2 washing circuits.

Electromechanical control panel with digital thermostat for setting both temperature and treatment time.

All models are equipped with **solenoid valve for automatic tank filling** and **oil separator disc**.

The Sirius 1000 and Sirius 1200 models are also equipped with an **electric vapour extractor**.



Transport wheels

The machine is supported on 4 wheels that allow the machine to be moved and kept at the right height for positioning the trolley.



Electric extractor fan

The Sirius 1000 and Sirius 1200 models are equipped as standard with an electric steam extractor as well as a door locking system to block early opening when the wash chamber is full of hot steam.



Loading trolley

Transport trolley with wheels and guides so that it can be moved, even when the wash tray is loaded. This facilitates the loading and unloading of material into and out of the washer.

Supplied as standard on the Sirius 1200 model.

Equipment

Double washing circuit



Oil separator disc



Filling solenoid valve



TECHNICAL DATA

	Sirius 600	Sirius 800	Sirius 1000	Sirius 1200
Basket diameter	550 mm	750 mm	900 mm	1.130 mm
Washing height	350 mm	450 mm	450 mm	600 mm
Loading capacity	150 Kg	300 Kg	300 Kg	450 Kg
Power supply	400V - 3 PH - 50 Hz			
Vapour extractor	Not available		0,75 Kw	
Pump pressure	3 bar	3 bar	3 bar	3 bar
Tank capacity	60 litres	80 litres	80 litres	200 litres
Heating	1x 5Kw	1x 7.5 Kw	1x 7.5 Kw	2x 7.5 Kw
Thermostat	0-60°C		0-90° C	
Material	Aisi 430			
Packaging	950x800x1100	1300x1600x1300	1300x1420x1400	1500x1620x1600
Weight	120 Kg	150 Kg	300 Kg	400 Kg